

unplanned. Alternatively, the notification including the written documentation may be made in writing and sent so that it is received by the Administrator at least 7 calendar days prior to refilling.

(3) *Notification waiver.* Where a notification required by paragraphs (c)(1) or (2) of this section is sent to a delegated State or local agency, a copy of the notification to the Administrator is not required. A delegated State or local agency may waive the requirements for these notifications.

(d) *Compliance certification.* For sources subject to the compliance certification provisions of title V, a recertification of continuous compliance with §§ 65.43(b)(1) and 65.44(b)(1) shall be based on the annual inspections required by § 65.43(c)(1)(i) and (c)(2)(ii)(A) and any observations made at other times when the roof is viewed.

§§ 65.49–65.59 [Reserved]

Subpart D—Process Vents

§ 65.60 Applicability.

The provisions of this subpart and of subpart A of this part apply to regulated material emissions from process vents where a referencing subpart references the use of this subpart.

§ 65.61 Definitions.

All terms used in this subpart shall have the meaning given them in the Act and in subpart A of this part. If a term is defined in both subpart A of this part and in other subparts that reference the use of this subpart, the term shall have the meaning given in subpart A of this part for purposes of this subpart.

§ 65.62 Process vent group determination.

(a) *Group status.* The owner or operator of a process vent shall determine the group status (i.e., Group 1, Group 2A, or Group 2B) for each process vent. Group 1 process vents require control, and Group 2A and 2B process vents do not. Group 2A process vents require parameter monitoring, and Group 2B process vents do not. The owner or operator shall report the group status of

each process vent as specified in § 65.5(c)(2).

(b) *Group 1.* A process vent is considered Group 1 if it meets at least one of the following specifications:

(1) The owner or operator designates the process vent as Group 1.

(2) At representative operating conditions expected to yield the lowest TRE index value for the process vent, the TRE index value is less than or equal to 1.0, the flow rate is greater than or equal to 0.011 standard cubic meter per minute (0.40 standard cubic foot per minute), and the concentration is greater than or equal to the applicable criterion in table 1 of this subpart. Procedures for determining the TRE index value, flow rate, and concentration are specified in § 65.64.

(c) *Group 2A.* A process vent is considered Group 2A if, at representative operating conditions expected to yield the lowest TRE index value, it has a TRE index value of greater than 1.0 and less than or equal to 4.0, a flow rate of greater than or equal to 0.011 standard cubic meter per minute (0.40 standard cubic foot per minute), and a concentration greater than or equal to the applicable table 1 criterion. Procedures for determining the TRE index value, flow rate, and concentration are specified in § 65.64.

(d) *Group 2B.* A process vent is considered Group 2B if, at representative operating conditions expected to yield the lowest TRE index value, it has a TRE index value of greater than 4.0; or a flow rate of less than 0.011 standard cubic meter per minute (0.40 standard cubic foot per minute); or a concentration less than the applicable criterion in table 1 of this subpart. Procedures for determining the TRE index value, flow rate, and concentration are specified in § 65.64.

§ 65.63 Performance and group status change requirements.

(a) *Group 1 performance requirements.* Except for the additional requirement for halogenated vent streams as provided in paragraph (b) of this section, the owner or operator of a Group 1 process vent shall comply with the requirements of either paragraph (a)(1), (2), or (3) of this section.